

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2022


Version number 27 (replaces version 26)


Revision: 03.03.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** MÄDLER Aluminium Spray
- **Article number:** 14070106 (OPN-Art.-No. 63020)
- **Unique formula identifier (UFI):** 0JHM-V5RP-Q00M-TQSD
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Coating compound/ Surface coating/ paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer:**  
OPN-CHEMIE GmbH  
In der Au 14  
D-57290 Neunkirchen/Germany  
Tel.: +49 (0) 2735 / 7725-0  
Fax: +49 (0) 2735 / 7725-90
- **Supplier:**  
MÄDLER GmbH  
Tränkestraße 6-8  
D-70597 Stuttgart/Germany  
Tel.: +49 (0) 711 720 95 - 0  
Fax: +49 (0) 711 720 95 - 33
- **Further information obtainable from:**  
Safety data sheets Mrs. Barbara Angelika Gros-Petri  
Tel.: +49 (0) 2735 / 7725-20  
E-Mail: baerbel.petri@opn-chemie.de
- **Responsible at MÄDLER:**  
MÄDLER Product management, Mr. Knut Schmidt  
Tel.: +49 (0) 211 97 47 1-16  
E-Mail: duesseldorf@maedler.de
- **1.4 Emergency telephone number:**  
Emergency information service Vergiftungs-Informationen-Zentrale Freiburg +49 (0) 761 / 1 92 40

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- 

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
-----------	-----------	--
- 

Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



- **Signal word** Danger
- **Hazard-determining components of labelling:**  
acetone  
xylene  
Hydrocarbons, C9, aromatics  
n-butyl acetate

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 27 (replaces version 26)

Revision: 03.03.2022

**Trade name: MÄDLER Aluminium Spray**

(Contd. of page 1)

**· Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**· Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapours or spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P501 Dispose of contents / container in accordance with national regulations of the disposal.

**· Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

**· 2.3 Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

**· 3.2 Mixtures****· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane, pure ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	5-<10%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 27 (replaces version 26)

Revision: 03.03.2022

**Trade name: MÄDLER Aluminium Spray**

(Contd. of page 2)

CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5-<5%
EINECS: 231-072-3 Reg.nr.: 01-2119529243-45-xxxx	aluminium powder (stabilized) Flam. Sol. 2, H228; Water-react. 2, H261	2.5-<5%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	2.5-<5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**  
Supply fresh air; consult doctor in case of complaints.  
Take affected persons into fresh air and keep quiet.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
Immediately remove any clothing soiled by the product.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
Breathing difficulty  
Headache  
Dizziness  
Dizziness  
Nausea
- **4.3 Indication of any immediate medical attention and special treatment needed**  
If swallowed or in case of vomiting, danger of entering the lungs.  
Later observation for pneumonia and pulmonary oedema.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Fire-extinguishing powder  
Carbon dioxide  
Use fire extinguishing methods suitable to surrounding conditions.  
Foam
- **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**  
Cool endangered receptacles with water spray.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Keep away from ignition sources.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 27 (replaces version 26)

Revision: 03.03.2022

Trade name: MÄDLER Aluminium Spray

(Contd. of page 3)

### · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

### · 6.4 Reference to other sections

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.  
Avoid contact with skin and eyes.

### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

### · 7.2 Conditions for safe storage, including any incompatibilities

#### · Storage:

#### · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

#### · Information about storage in one common storage facility: Not required.

#### · Further information about storage conditions: Protect from heat and direct sunlight.

### · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### · 8.2 Exposure controls

#### · Ingredients with limit values that require monitoring at the workplace:

##### CAS: 67-64-1 acetone

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm
	Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm

##### CAS: 106-97-8 butane, pure

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm
	Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

##### CAS: 123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm
	Long-term value: 724 mg/m <sup>3</sup> , 150 ppm

##### CAS: 1330-20-7 xylene

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 220 mg/m <sup>3</sup> , 50 ppm
	Sk, BMGV

##### CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 274 mg/m <sup>3</sup> , 50 ppm
	Sk

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 27 (replaces version 26)

Revision: 03.03.2022

**Trade name: MÄDLER Aluminium Spray**

(Contd. of page 4)

**CAS: 141-78-6 ethyl acetate**

WEL	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm
	Long-term value: 734 mg/m <sup>3</sup> , 200 ppm

**· DNELs****CAS: 67-64-1 acetone**

Oral	DNEL	62 mg(kg (ME)
Inhalative	DNEL	200 mg/m <sup>3</sup> (ME)

**· Ingredients with biological limit values:****CAS: 1330-20-7 xylene**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

- **Additional information:** The lists valid during the making were used as basis.
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
  - Avoid contact with the eyes.
  - Avoid contact with the eyes and skin.
- **Respiratory protection:**
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
  - Not necessary if room is well-ventilated.
- **Recommended filter device for short term use:** Filter AX
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
  - Butyl rubber, BR
  - Recommended thickness of the material:  $\geq 0.7$  mm
- **Penetration time of glove material**
  - $\geq 60$  min
  - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection**



Tightly sealed goggles

- **Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Aerosol

(Contd. on page 6)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 27 (replaces version 26)

Revision: 03.03.2022

**Trade name: MÄDLER Aluminium Spray**

(Contd. of page 5)

· <b>Colour:</b>	Silver-coloured
· <b>Odour:</b>	Solvent-like
· <b>Odour threshold:</b>	Not determined.
· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Boiling point or initial boiling point and boiling range</b>	Not applicable, as aerosol.
· <b>Flammability</b>	Not applicable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	Not determined.
· <b>Upper:</b>	Not determined.
· <b>Flash point:</b>	Not applicable, as aerosol.
· <b>Ignition temperature:</b>	>200 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>Dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure:</b>	Not determined.
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C:</b>	0.72527 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Aerosol
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Auto-ignition temperature:</b>	Not determined.
· <b>Explosive properties:</b>	Not determined.
· <b>Solvent separation test:</b>	
· <b>Organic solvents:</b>	93.1 %
· <b>VOC (EC)</b>	675.2 g/l
· <b>Solids content:</b>	0.0 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not applicable.

· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void

(Contd. on page 7)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 27 (replaces version 26)

Revision: 03.03.2022

**Trade name: MÄDLER Aluminium Spray**

(Contd. of page 6)

- |                           |      |
|---------------------------|------|
| · Corrosive to metals     | Void |
| · Desensitised explosives | Void |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

#### · LD/LC50 values relevant for classification:

##### ATE (Acute Toxicity Estimates)

Dermal	LD50	17,377 mg/kg
Inhalative	LC50/4 h	174 mg/l

##### CAS: 67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	~76 mg/l (rat)

##### CAS: 74-98-6 propane

Inhalative	LC50/4 h	>20 mg/l (rat)
------------	----------	----------------

##### CAS: 106-97-8 butane, pure

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

##### CAS: 123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

##### CAS: 75-28-5 isobutane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

##### CAS: 1330-20-7 xylene

Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)

##### Hydrocarbons, C9, aromatics

Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rat)
Inhalative	LC50/4 h	>6,193 mg/l (rat)

##### CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 27 (replaces version 26)

Revision: 03.03.2022

**Trade name: MÄDLER Aluminium Spray**

(Contd. of page 7)

Inhalative	LC50/4 h	35.7 mg/l (rat)
<b>CAS: 141-78-6 ethyl acetate</b>		
Oral	LD50	5,620 mg/kg (rabbit)
Dermal	LD50	>20,000 mg/kg (rat)
Inhalative	LC50/4 h	1,600 mg/l (rat)

- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |                                       |                     |
|---------------------------------------|---------------------|
| · <b>14.1 UN number or ID number</b>  | UN1950              |
| · <b>ADR/RID/ADN, IMDG, IATA</b>      |                     |
| · <b>14.2 UN proper shipping name</b> | UN1950 AEROSOLS     |
| · <b>ADR/RID/ADN</b>                  | AEROSOLS            |
| · <b>IMDG</b>                         | AEROSOLS            |
| · <b>IATA</b>                         | AEROSOLS, flammable |

(Contd. on page 9)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 27 (replaces version 26)

Revision: 03.03.2022

Trade name: MÄDLER Aluminium Spray

(Contd. of page 8)

## · 14.3 Transport hazard class(es)

## · ADR/RID/ADN



· Class 2 5F Gases.  
 · Label 2.1

## · IMDG, IATA



· Class 2.1 Gases.  
 · Label 2.1

## · 14.4 Packing group

· ADR/RID/ADN, IMDG, IATA Void

## · 14.5 Environmental hazards:

· Marine pollutant: No

## · 14.6 Special precautions for user

## · Hazard identification number (Kemler code):

## · EMS Number:

## · Stowage Code

Warning: Gases.

-

F-D,S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

## · Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre:  
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:  
 Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

## · 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

## · Transport/Additional information:

## · ADR/RID/ADN

## · Limited quantities (LQ)

## · Excepted quantities (EQ)

1L

Code: E0

Not permitted as Excepted Quantity

## · Transport category

## · Tunnel restriction code

2

D

## · IMDG

## · Limited quantities (LQ)

## · Excepted quantities (EQ)

1L

Code: E0

Not permitted as Excepted Quantity

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 27 (replaces version 26)

Revision: 03.03.2022

Trade name: MÄDLER Aluminium Spray

(Contd. of page 9)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H261 In contact with water releases flammable gases.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3

(Contd. on page 11)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.03.2022

Version number 27 (replaces version 26)

Revision: 03.03.2022

**Trade name: MÄDLER Aluminium Spray**

(Contd. of page 10)

Flam. Sol. 2: Flammable solids – Category 2  
Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3  
· **\* Data compared to the previous version altered.**

GB