

PTFE Trockenschmierung Spray

Print date	16.01.2023
Revision date	16.01.2023
Version	8.0 (en)
replaces version of	01.12.2022 (7.6)

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

* 1.1 Product identifier

Trade name/designation PTFE Trockenschmierung Spray

- * 1.2 Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture Lubricant (dry lubrication)
- Remark UFI: 8CDQ-7E13-X001-34Y0

1.3 Details of the supplier of the safety data sheet

Manufacturer

F.W.Klever Hauptstraße 20 D-84168 Aham Telephone +49 (0) 8744 96 99 10 Telefax + 49 (0) 8744 96 99 96 E-mail info@ballistol.de Website www.ballistol.de

Department responsible for information: Qualitätssicherung Telephone +49 (0) 8744 96 99 80

E-mail (competent person): info@ballistol.de

* 1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK GmbH +

+49 (0)6132-84463

* SECTION 2: Hazards identification

* 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP] Classification procedure

Aerosol 1, H222 H229 Eye Irrit. 2, H319

Hazard statements for physical hazards

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Hazard statements for health hazards

H319 Causes serious eye irritation.

* 2.2 Label elements

* Labelling according to Regulation (EC) No. 1272/2008 [CLP]



ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

PTFE Trockenschmierung Spray

Print date	16.01.2023
Revision date	16.01.2023
Version	8.0 (en)
replaces version of	01.12.2022 (7.6)

Hazard pictograms



Signal word Danger

Hazard statements

H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation.

Precautionary statements

P102 Keep out of reach of children.

P251 Do not pierce or burn, even after use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to recycling

2.3 Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

Hazardous ingredients

CAS No.	EC No.	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL/ M/ ATE
74-98-6	200-827-9	propane	35 weight-%	Flam. Gas 1; H220 Press. Gas	
106-97-8	203-448-7	butane	15 weight-%	Flam. Gas 1; H220 Press. Gas	

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. Remove affected person from the danger area and lay down.

Following inhalation

Provide fresh air.

Following skin contact

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.



ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

PTFE Trockenschmierung Spray

Print date	16.01.2023
Revision date	16.01.2023
Version	8.0 (en)
replaces version of	01.12.2022 (7.6)

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Call a physician immediately.

Following ingestion

Rinse mouth immediately and drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

Unconsciousness Inebriation Vomiting Nausea Dizziness Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Foam Carbon dioxide (CO2) Water spray jet

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products Carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters In case of fire: Wear self-contained breathing apparatus. Wear full chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Heating causes rise in pressure with risk of bursting

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Provide adequate ventilation. Use personal protection equipment. Remove all sources of ignition.



PTFE Trockenschmierung Spray

Print date	16.01.2023
Revision date	16.01.2023
Version	8.0 (en)
replaces version of	01.12.2022 (7.6)

6.2 Environmental precautions

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For containment

Suitable material for taking up: Sawdust Take up mechanically and send for disposal.

6.4 Reference to other sections

No data available

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

No special measures are necessary. Keep away from sources of ignition - No smoking. Do not inhale aerosols Avoid: Eye contact

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Storing of food in workroom forbidden. Wash hands before breaks and after work.

7.2 Conditions for safe storage, including any incompatibilities

Storage class

2B Aerosol dispensers and lighters

Materials to avoid

Do not store together with: Food and feedingstuffs

Further information on storage conditions Protect of heat.

7.3 Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

•	•		
CAS No.	EC No.	Substance name	occupational exposure limit value
106-97-8	203-448-7	n-Butane	600 [ml/m³(ppm)] 1450 [mg/m³] Short-term(ml/m³) 750 Short-term(mg/m³) 1810 (UK)
106-97-8	203-448-7	n-Butane	Short-term(ml/m³) 1000 (1) (1) 15 minutes average value (IE)



PTFE Trockenschmierung Spray

Print date	16.01.2023
Revision date	16.01.2023
Version	8.0 (en)
replaces version of	01.12.2022 (7.6)

8.2 Exposure controls Personal protection equipment

Eye/face protection

tightly fitting goggles

Hand protection Gloves (solvent-resistant)

Body protection:

Protective clothing

Respiratory protection

Respiratory protection necessary at: insufficient ventilation Suitable respiratory protection apparatus: Short term: filter apparatus, Filter A/P2

Environmental exposure controls

Technical measures to prevent exposure

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Aerosol

Colour

colourless clear

Odour

like: Alcohol

Safety relevant basis data

	Value	Method	Source, Remark
Odour threshold:	not determined		
Melting point/freezing point	not determined		
Boiling point or initial boiling point and boiling range	approx. 78 °C pressure 1013 mbar		
flammability	not determined		
Lower and upper explosion limit	Upper explosion limit 10.9 Vol-%		(Propan)
Lower and upper explosion limit	Lower explosion limit 1.5 Vol-%		(Propan)
Flash point Auto-ignition temperature Decomposition temperature	approx104 °C not determined not determined		(Propan)



ES WIRKT.

PTFE Trockenschmierung Spray Print date 16 01 2023

Print date	16.01.2023
Revision date	16.01.2023
Version	8.0 (en)
replaces version of	01.12.2022 (7.6)

	Value	Method	Source, Remark
рН	in delivery state approx. 7.5 (20°C)		neutral
Viscosity	not determined		
Solubility(ies)	Water solubility		multimiscible
Partition coefficient n- octanol/water (log value)	not determined		
Vapour pressure	approx. 60 hPa (20°C)		
Density and/or relative density			information concerns to liquid phase
Relative vapour density	not determined		
particle characteristics	not determined		

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

No data available

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Container under pressure. Protect from direct exposure to sunlight and temperatures exceeding 50°C/122°F. Evolution of highly flammable gases/vapours.

10.5 Incompatible materials

Oxidising agent, strong

10.6 Hazardous decomposition products

Carbon monoxide Carbon dioxide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Animal data			
	Effective dose	Method, Evaluation	Source, Remark
Acute oral toxicity	> 5000 mg/kg Species Rat		Data apply to the main component.
Acute dermal toxicity	> 2000 mg/kg Species Rat		Data apply to the main component.



PTFE Trockenschmierung Spray Print date 16.01.2023

16.01.2023
16.01.2023
8.0 (en)
01.12.2022 (7.6)

	•		()
	Effective dose	Method,Evaluation	Source, Remark
Acute inhalation toxicity	> 20000 mg/L Species Rat Exposure time 4 h		Details refer to the main component
Skin corrosion/irritation			
Animal data			
Result / Evaluation	Method	Source, Remark	
non-irritant.			
Serious eye damage/irritation			
Animal data			
Result / Evaluation	Method	Source, Remark	
Irritant.			
Sensitisation to the respiratory tra	ct		
not determined			
Skin sensitisation			
Animal data			
Result / Evaluation	Dose / Concentration	Method	Source, Remark
not sensitising.			experiences
Germ cell mutagenicity			
not determined			
Carcinogenicity			
not determined			
Reproductive toxicity			
not determined			
STOT-single exposure			
not determined			
STOT-repeated exposure			
not determined			
Aspiration hazard			
not determined			
11.2 Information on other hazards			
No data available			
SECTION 12: Ecological inform	ation		
12.1 Toxicity			
Aquatic toxicity			
	Effective dose	Method,Evaluation	Source, Remark
Acute (short-term) fish toxicity	LC50: > 8100 mg/L Species Leuciscus idus (golden orfe) Test duration 48 h		

Chronic (long-term) fish toxicity not determined



ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

PTFE Trockenschmierung Spray

Print date	16.01.2023
Revision date	16.01.2023
Version	8.0 (en)
replaces version of	01.12.2022 (7.6)

	Effective dose	Method,Evaluation	Source, Remark
Acute (short-term) toxicity to crustacea	EC50 > 9000 mg/L Species Daphnia magna (Big water flea) Test duration 48 h	OECD	
Chronic (long-term) toxicity to aquatic invertebrate	not determined		
Acute (short-term) toxicity to algae and cyanobacteria	EC10 > 6500 mg/L Species Pseudomonas putida Test duration 16 h		
Chronic (long-term) toxicity to aquatic algae and cyanobacteria	not determined		
Toxicity to other aquatic plants/organisms	not determined		
Toxicity to microorganisms	not determined		
Persistence and degradability			
	Value	Mathad	Source Demark

	Value	Method	Source, Remark
Biodegradation			Readily biodegradable (according to OECD criteria).

12.3 Bioaccumulative potential

- No data available
- 12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Additional ecotoxicological information

Additional information

Do not allow uncontrolled discharge of product into the environment. The breakdown properties of the product have not been tested. The information on these is given on the basis of details in the literature.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste codes/waste designations according to EWC/AVV

Waste code product Waste name

140603 * other solvents and solvent mixtures

Appropriate disposal / Package

Completely emptied packages can be recycled. Recycle sales packaging via DSD (Duales System Deutschland).



PTFE Trockenschmierung Spray

Print date	16.01.2023
Revision date	16.01.2023
Version	8.0 (en)
replaces version of	01.12.2022 (7.6)

Remark

Send to a hazardous waste incinerator facility under observation of official regulations.

SECTION 14: Transport information Land transport Sea transport (IMDG) Air transport (ICAO-TI / IATA-(ADR/RID) DGR) 14.1 UN number or ID number UN 1950 UN 1950 UN 1950 14.2 UN proper shipping **AEROSOLS AEROSOLS** Aerosols, flammable name 14.3 Transport hazard 2.1 2.1 2.1 class(es) 14.4 Packing group -_ _ 14.5 Environmental hazards No No No 14.6 Special precautions for user

No data available

14.7 Maritime transport in bulk according to IMO instruments

No data available

Land transport (ADR/RID)

• • •	
UN number or ID number	UN 1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Hazard label(s)	2.1
Classification code	5F
Packing group	-
Environmental hazards	No
Limited quantity (LQ)	1 L
Special provisions	190, 327, 344, 625
Tunnel restriction code	D

Sea transport (IMDG)

UN number or ID number	UN 1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Packing group	-
Environmental hazards	No
Limited quantity (LQ)	1 L
Marine pollutant	No
EmS	F-D, S-U

Air transport (ICAO-TI / IATA-DGR)

UN number or ID number	UN 1950
UN proper shipping name	Aerosols, flammable



PTFE Trockenschmierung Spray Print date 16 01 2023

Print date	16.01.2023
Revision date	16.01.2023
Version	8.0 (en)
replaces version of	01.12.2022 (7.6)

Transport hazard class(es)2.1Packing group-Environmental hazardsNo

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No data available

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information

Additional information

National and local regulations concerning chemicals shall be observed.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Relevant H- and EUH-phrases (Number and full text)

H220 Extremely flammable gas.

Indication of changes

* Data changed compared with the previous version